

Ficha Técnica

MODELO:
CONTROLADOR:

Horno CS 130 litros
Bartlett Modelo Genesis Spark



APLICACIONES

*Cerámica.
*Vitrofundición.

CARACTERÍSTICAS

El Genesis Spark de Bartlett Instrument es un controlador táctil compacto, ideal para hornos con una sola zona de temperatura. Incorpora una pantalla a color intuitiva que facilita la navegación y programación, con descripciones claras y niveles de interfaz ajustables para distintos tipos de usuarios. Permite guardar hasta 30 programas personalizados, cada uno con 32 segmentos, y ofrece opciones avanzadas como modificar rampas, añadir tiempo o temperatura y saltar fases durante la cocción. Incluye funciones de diagnóstico automático, alarmas, registro de mantenimiento y códigos de error para mayor seguridad. Cuenta con conectividad Wi-Fi para actualizaciones de software y monitoreo remoto mediante aplicación móvil. Opera con termopares tipo K (también compatibles con S o R), ofrece una precisión de $\pm 5^{\circ}\text{C}$, soporta temperaturas de hasta 1288°C , y trabaja en rangos de 0 a 52°C . El Genesis Spark combina tecnología moderna, facilidad de uso y alto rendimiento en un formato compacto.

MEDIDAS CÁMARA INTERNA:

ALTO: 69cm

DIÁMETRO INTERNO: 53cm

MEDIDAS EXTERNAS:

ALTO: 95cm

DIÁMETRO EXTERNO: 74cm

VOLUMEN: 130 litros

POTENCIA: 11000 Watts

MATERIAL CÁMARA INTERNA: Ladrillos refractarios de alta alúmina

TERMOPAR: Tipo K con revestimiento cerámico.

TEMPERATURA MÁXIMA: 1288°C

ELEMENTOS CALEFACTORES: Alambre espiral de aleación tipo Kanthal

CORRIENTE: 50A

TENSIÓN: 220V

GARANTÍA:

Dos años contra defectos de fabricación

Tecnical Datasheet

MODEL:
CONTROLLER:

CS Kiln 130 Liters

Bartlett Model Genesis Spark



APPLICATIONS

*Ceramics.
*Glassfusing.

CHARACTERISTICS

The Genesis Spark from Bartlett Instrument is a compact touch controller, ideal for kilns with a single temperature zone. It features an intuitive color display that makes navigation and programming easy, with clear descriptions and adjustable interface levels for different types of users. It can store up to 30 custom programs, each with 32 segments, and offers advanced options such as modifying ramps, adding time or temperature, and skipping phases during firing. It includes automatic diagnostics, alarms, maintenance logs, and error codes for increased safety. It also has Wi-Fi connectivity for software updates and remote monitoring via a mobile app. It operates with type K thermocouples (also compatible with S or R), offers ± 5 °C accuracy, supports temperatures up to 1288 °C, and operates in ambient ranges from 0 to 52 °C. The Genesis Spark combines modern technology, ease of use, and high performance in a compact format.

INTERNAL CHAMBER DIMENSIONS:

HEIGHT: 69 cm

WIDTH: 53cm

EXTERNAL DIMENSIONS:

HEIGHT: 95cm

WIDTH: 74cm

VOLUME: 130 litros

POWER: 11000 Watts

INTERNAL CHAMBER MATERIAL: High Alumina Refractory Bricks

THERMOCOUPLE: Type K with Ceramic Coating

MAXIMUM TEMPERATURE: 1288°C

HEATING ELEMENTS: Kanthal-Type Alloy Spiral Wire

CURRENT: 50A

VOLTAGE: 220V

WARRANTY:

Two-Year Warranty Against Manufacturing Defects